



## HP 2.26 C5

PORTABLE POWER

WATERPUMP Range AQUALINE SPECIALIST

### PRODUCT ADVANTAGES

- HONDA Professional Engine
- Automatic priming
- Solid and high-performance equipment
- Offeres accessories
- High-pressure equipment

With nearly 6 bar of pressure, the HP 2.26 H can be used for high-pressure cleaning of machinery, such as agricultural vehicles. When combined with the nozzle kit, it can be used to suppress fires.

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

### Range AQUALINE SPECIALIST

High performance under extreme conditions.



## HP 2.26 C5

### WATER PUMP SPECIFICATIONS

|  |                     |
|--|---------------------|
| Range                                  | AQUALINE SPECIALIST |
| Type liquid                            | High voltage use    |
| Suction diameter [mm]                  | 50                  |
| Backflow diameter (mm)                 | 50                  |
| Outflow maximum (L/min)                | 440                 |
| Outflow maximum (m3/h)                 | 26,40               |
| Lifting height (m)                     | 57                  |
| Suction height (m)                     | 8                   |
| Granulometry (mm)                      | 8                   |
| Automatic priming                      | Yes                 |
| Fuel                                   | Petrol              |
| Tank (L)                               | 3,10                |
| 75% cons. (l/h) *                      | 0,90                |
| 75% Autonomy (h) *                     | 3,40                |
| Sound power level guaranteed LwA dB(A) | 108                 |
| Acoustic pressure level @1m in dB(A)   | 92                  |
| Acoustic pressure level @7m in dB(A)   | 77                  |

### ENGINE SPECIFICATIONS

|   |          |
|---|----------|
| Engine brand                              | HONDA    |
| Engine ref.                               | GX160_C5 |
| Engine Type                               | O.H.V.   |
| Start                                     | Starter  |
| Oil shutdown                              | Oui      |
| Displacement (cm3)                        | 163      |
| Oil system capacity including filters (l) | 0,60     |

### DIMENSIONS AND WEIGHT

|                 |       |
|-----------------|-------|
| Length (cm)     | 41,50 |
| Width (cm)      | 54,50 |
| Height (cm)     | 45,50 |
| Dry Weight (kg) | 30    |

### PACKAGING

|                                    |        |
|------------------------------------|--------|
| Packaging type                     | Box    |
| Length (cm)                        | 54     |
| Width (cm)                         | 42     |
| Height (cm)                        | 45     |
| Weight (kg)                        | 35     |
| Pallet type                        | 120/80 |
| Number of box by pallet            | 12     |
| Pallet height (cm)                 | 148    |
| weight of the packaged Pallet (kg) | 430    |

### ACCESSORIES SUPPLIED



|                     |
|---------------------|
| Inlet filter        |
| Screw-on connectors |



|                             |
|-----------------------------|
| Circlips                    |
| User and maintenance manual |



### OPTIONS



|               |   |
|---------------|---|
| <b>RBH1</b>   | Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)  |
| <b>RBH0-5</b> | Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).   |
| <b>RHO</b>    | Cover for SDMO 's generating sets, welding sets and water pumps   |
| <b>R09</b>    | Fire-fighting kit for HP 2.26 H pumpos with 2 fire hose connectors, 25 m fire hose, 5 m intake hose and fire lance. |