



## TR 2.36 C5

PORTABLE POWER

WATERPUMP Range AQUALINE INTENS

### PRODUCT ADVANTAGES

- HONDA Professional Engine
- Resistant pump-barrel
- Automatic priming
- Easy acces to the turbine
- Offeres accessories

The AQUALINETM INTENS TR 2.36 H and TR 3.60 H models have a very high quality pump body and are designed for treating dirty water intensively and reliably. The front cover can be removed for quick cleaning, which is a considerable help for professionals.

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

### Range AQUALINE INTENS

Designed for water with low solid content.



## TR 2.36 C5

### WATER PUMP SPECIFICATIONS

|  |                               |
|--|-------------------------------|
| Range                                  | AQUALINE INTENS               |
| Type liquid                            | Heavily sedimented water pump |
| Suction diameter [mm]                  | 50                            |
| Backflow diameter (mm)                 | 50                            |
| Outflow maximum (L/min)                | 600                           |
| Outflow maximum (m3/h)                 | 36                            |
| Lifting height (m)                     | 29                            |
| Suction height (m)                     | 8                             |
| Granulometry (mm)                      | 8                             |
| Automatic priming                      | Yes                           |
| Fuel                                   | Petrol                        |
| Tank (L)                               | 2                             |
| 75% cons. (l/h) *                      | 1                             |
| 75% Autonomy (h) *                     | 2                             |
| Sound power level guaranteed LwA dB(A) | 103                           |
| Acoustic pressure level @1m in dB(A)   | 87                            |
| Acoustic pressure level @7m in dB(A)   | 72                            |

### ENGINE SPECIFICATIONS

|   |          |
|---|----------|
| Engine brand                              | HONDA    |
| Engine ref.                               | GX120_C5 |
| Engine Type                               | O.H.V.   |
| Start                                     | Starter  |
| Oil shutdown                              | Oui      |
| Displacement (cm3)                        | 118      |
| Oil system capacity including filters (l) | 0,60     |

### DIMENSIONS AND WEIGHT

|                 |       |
|-----------------|-------|
| Length (cm)     | 46,80 |
| Width (cm)      | 36,20 |
| Height (cm)     | 39,80 |
| Dry Weight (kg) | 23    |

### PACKAGING

|                                    |        |
|------------------------------------|--------|
| Packaging type                     | Box    |
| Length (cm)                        | 48     |
| Width (cm)                         | 38     |
| Height (cm)                        | 41,50  |
| Weight (kg)                        | 26,50  |
| Pallet type                        | 120/80 |
| Number of box by pallet            | 12     |
| Pallet height (cm)                 | 138    |
| weight of the packaged Pallet (kg) | 328    |

### ACCESSORIES SUPPLIED



|                     |
|---------------------|
| Inlet filter        |
| Screw-on connectors |



|                             |
|-----------------------------|
| Circlips                    |
| User and maintenance manual |



### OPTIONS



|               |   |
|---------------|---|
| <b>RBH1</b>   | Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)    |
| <b>RBH0-5</b> | Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).   |
| <b>RHO</b>    | Cover for SDMO 's generating sets, welding sets and water pumps |
| <b>R11</b>    | Piping kit for 2 water pumps made up of 5m suction + 25m lift.  |
| <b>R13</b>    | Rapid connections kit for 2 water pumps.                        |