



# TR 3.60 C5 PORTABLE POWER WATERPUMP Range AQUALINE INTENS

#### **PRODUCT ADVANTAGES**

- HONDA Professional Engine
- · Resistant pump-barrel
- Automatic priming
- · Easy acces to the turbine
- Offeres accessories

The AQUALINETM INTENS TR 2.36 H and TR 3.60 H models have a very high quality pump body and are designed for treating dirty water intensively and reliably. The front cover can be removed for quick cleaning, which is a considerable help for professionals.

STAGE V (2016/1628 EU): This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

#### Range AQUALINE INTENS

Designed for water with low solid content.

















### TR 3.60 C5

#### WATER PUMP SPECIFICATIONS

| Range                                  | AQUALINE INTENS               |
|--|-------------------------------|
| Type liquid                            | Heavily sedimented water pump |
| Suction diameter [mm]                  | 76                            |
| Backflow diameter (mm)                 | 76                            |
| Outflow maximum (L/min)                | 900                           |
| Outlflow maximum (m3/h)                | 54                            |
| Lifting height (m)                     | 26                            |
| Suction height (m)                     | 8                             |
| Granulometry (mm)                      | 8                             |
| Automatic priming                      | Yes                           |
| Fuel                                   | Petrol                        |
| Tank (L)                               | 3,10                          |
| 75% cons. (I/h) *                      | 0,90                          |
| 75% Autonomy (h) *                     | 3,40                          |
| Sound power level guaranteed LwA dB(A) | 105                           |
| Acoustic pressure level @1m in dB(A)   | 91                            |
| Acoustic pressure level @7m in dB(A)   | 76                            |

#### **ENGINE SPECIFICATIONS**

| Engine brand                              | HONDA    |
|---|----------|
| Engine ref.                               | GX160_C5 |
| Engine Type                               | O.H.V.   |
| Start                                     | Starter  |
| Oil shutdown                              | Oui      |
| Displacement (cm3)                        | 163      |
| Oil system capacity including filters (I) | 0,60     |

#### **DIMENSIONS AND WEIGHT**

| Length (cm)     | 50,50 |
|-----------------|-------|
| Width (cm)      | 39,80 |
| Height (cm)     | 46,60 |
| Dry Weight (kg) | 29    |

#### **PACKAGING**

| Packaging type                     | Box    |
|------------------------------------|--------|
| Length (cm)                        | 51,50  |
| Width (cm)                         | 42     |
| Height (cm)                        | 48     |
| Weight (kg)                        | 34,50  |
| Pallet type                        | 120/80 |
| Number of box by pallet            | 12     |
| Pallet height (cm)                 | 157    |
| weight of the packaged Pallet (kg) | 424    |





## TR 3.60 C5

#### **ACCESSORIES SUPPLIED**



Inlet filter

**RBH0-5** 

**R12** 

**R14** 



Circlips



Screw-on connectors



User and maintenance manual



RBH1 Box of 24 o.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



RHO Cover for SDMO 's generating sets, welding sets and water pumps



Piping kit for 3 water pumps made up of 5 m suction + 25 m lift.



Rapid connections kit for 3 water pumps.

