KOHLER_® **SDMO**_®



XT 3.78 C5

PORTABLE POWER WATERPUMP Range AQUALINE SPECIALIST

PRODUCT ADVANTAGES

- HONDA Professional Engine
- Easy acces to the turbine (without tools)
- Automatic priming
- Resistant pump-barrel
- Offeres accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range AQUALINE SPECIALIST High performance under extreme conditions.



XT 3.78 C5

WATER PUMP SPECIFICATIONS

Range	AQUALINE SPECIALIST		
Type liquid	Extremely heavily sedimented water pump		
Suction diameter [mm]	76		
Backflow diameter (mm)	76		
Outflow maximum (L/min)	1340		
OutIflow maximum (m3/h)	80,40		
Lifting height (m)	27		
Suction height (m)	8		
Granulometry (mm)	27		
Automatic priming	Yes		
Fuel	Petrol		
Tank (L)	5,30		
75% cons. (l/h) *	2		
75% Autonomy (h) *	2,70		
Sound power level guaranteed LwA dB(A)	110		
Acoustic pressure level @1m in dB(A)	94		
Acoustic pressure level @7m in dB(A)	80		

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX240_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	242
Oil system capacity including filters (I)	1,10

DIMENSIONS AND WEIGHT

Length (cm)	69
Width (cm)	48,50
Height (cm)	53,20
Dry Weight (kg)	58

PACKAGING

Packaging typeBoxLength (cm)72Width (cm)52Height (cm)58Weight (kg)68,50Pallet type120/80
Width (cm) 52 Height (cm) 58 Weight (kg) 68,50
Height (cm) 58 Weight (kg) 68,50
Weight (kg) 68,50
Ballet type 120/80
rallet type 120/00
Number of box by pallet 4
Pallet height (cm) 129
weight of the packaged Pallet (kg) 284



XT 3.78 C5 - PORTABLE POWER - WATERPUMP AQUALINE SPECIALIST This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com



XT 3.78 C5

	Inlet filter		80	Circlips	
	Screw-on connec	ctors		User and maintenance manual	
OPTIONS					
	RHO	Cover for SDMO 's generating sets, welding sets and water pumps			
	R12	Piping kit for 3	water pumps made up of 5 i	m suction + 25 m lift.	
RÓP	R14	Rapid connect	ions kit for 3 water pumps.		



T 3.78 C5 - PORTABLE POWER - WATERPUMP AQUALINE SPECIALIST This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528. SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com